



EXTERIOR ELEVATION

FOUR-FOLD (FF701) HURICANE RATED DOOR SYSTEM

Designed for HVHZ applications
 Configuration Shown - EXTERIOR MOUNTED
 Operator: R Series, Electro-Mechanical

| OPENING WIDTHS | APPROX. CLEARANCES | | | | MAX TIME TO OPEN | MOTOR HP | OPERATOR STYLE |
|------------------|--------------------|----------|-------|-----|------------------|----------|----------------|
| | A | B | C | D | | | |
| 7'-6" to 10'-6" | 12" | 1/4 | 34.5" | 10" | 6.6 sec | 3/4 | R-XT |
| 10'-6" to 13'-6" | 12" | OPENING | 40" | 10" | 13.3 sec | 3/4 | R-XT |
| 13'-6" to 16'-0" | 12" | PLUS 18" | 44" | 10" | 13.3 sec | 3/4 | R-XT |



www.doorengineering.com
 1-800-959-1352

This layout is designed as a guide for required clearances for our Hurricane Rated, "Inside-Out" Four-Fold Door Systems. Maximum opening dimensions for a Hurricane Rated Four-Fold is 16' wide by 16' tall. REFER TO DRAWING RD0095-WL FOR PANEL LAYOUTS.